



Luxury High Gloss Synthetic Enamel

FEATURES / BENEFITS :

Luxury High Gloss Synthetic Enamel / Luxury Satin Enamel / Luxury Luster Enamel is based on blends premium quality oil based alkyds resins. It imparts a high opacity, excellent durability and forms a tough film, that is resistant to stains, water & chalking. It gives shiny new look to surface for years.

RECOMMENDED USAGE :

It can be used on interior and exterior surfaces. The Finish can be applied on wooden, metal and equivalent surfaces. It can also be used on machineries and equipments.

PAINTING :

Two coats on well primed & leveled surface at the interval of minimum 6 to 8 hours.

COVERAGE : DFT AFTER 2 COATS 40 TO 45 MICRONS :

Luxury High Gloss Enamel : 100 to 110 sq.ft. (2 coats).
Luxury Satin Enamel : 100 to 120 sq.ft. (2 coats).
Luxury Luster Enamel : 100 to 120 sq.ft. (2coats).

THINNER :

Use Champion Paints Thinner for Oil Based Paints.

DILUTION :

By Volume
8 to 10% (Brushing).
15 to 20% (Spraying).

SHADE RANGE :

As per colour-icon Fan-Deck (1800 shades). A special shade card is available.

GLOSS LEVEL :

Luxury High Gloss Enamel : 80-90 (At 20°GH.).
Luxury Satin Enamel : 15-35 (At 60°GH.).
Luxury Luster Enamel : 30-45 (At 60°GH.).

DRYING TIME :

Touch Dry : 10 Mins.
Tack Free : 2 Hours.
Hard Dry : Overnight (24 Hours).

PACKING SIZE :

50 ml., 100 ml., 200 ml., 500 ml., 1Lt., 4Lt., 10Lt., 20Lt.



Luxury High Gloss Synthetic Enamel

Surface Preparation :

Surface should be free from dust, dirt, grease, rust, moisture and loose particles for excellent result. Use appropriate primer & putty of Champion Paints for excellent leveling. Top coats of enamel can be brushed sprayed or applied by dipping. Use Champion Paints thinner. Apply two coats.

SAFETY PRECAUTION

Avoid contact with eyes and skin. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe in vapour or spray mist. This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge.

FIRST AID

- Eyes** : In the event of accidental splashes, flush eyes with warm water immediately and seek medical advise.
Skin : Wash skin thoroughly with soap and water or approved industrial cleaner. Do not use solvents or thinners.
Inhalation : Remove to fresh air, loosen collar and keep patient rested.
Ingestion : In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

For further safety information, please refer to our Material Safety Data Sheet. (MSDS).

DISCLAIMER !

The Information provided on this data sheet is not intended to be complete and is provided as general advise only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continues product development.

NOTE :- ADDITIONAL INFORMATION WILL BE AVAILABLE ON REQUEST.