

Crown Metal Primer - Red Oxide



FEATURES / BENEFITS

A Premium quality metal primer prepared from ideal blend of binders, high quality red oxide pigments & extenders which is used as an anti corrosive primer coat on metal surfaces.

RECOMMENDED USAGE

It can be used on all metal surfaces.

COVERAGE

Crown Metal Primer : 190 to 200 sq.ft. (1 coat).

SHADE RANGE

Dark Brown - Matt Finish.

GLOSS LEVEL

Crown Metal Primer - Matt Finish.

DRYING TIME :

Touch Dry : 30 Mins.
Tack Free : 3 Hours.
Hard Dry : Overnight (24 Hours).

PACKING SIZE

200 ml., 500 ml., 1 Lt., 4 Lt., 10 Lt., 20 Lt.

PAINTING

Single coat on well prepared surface.

DILUTION

By Volume
8 to 10% (Brushing).
15 to 20% (Spraying).

THINNER

Use Champion Paints Thinner or Mineral Turpentine Oil.

(Thinner no.101).

SURFACE PREPRATION

Surface should be free from dust, dirt, grease, rust, moisture and loose particles for excellent results.



Crown Metal Primer - Red Oxide

SAFETY PRECAUTION

Avoid contact with eyes and skin. Wear suitable protective clothing such as overalls, goggles, dust mask, and gloves. Use barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe in vapour or spray mist. This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge.

FIRST AID

Eyes : In the event of accidental splashes, flush eyes with warm water immediately and seek medical advise.
Skin : Wash skin thoroughly with soap and water or approved industrial cleaner. Do not use solvents or thinners.
Inhalation : Remove to fresh air, loosen collar and keep patient rested.
Ingestion : In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

For further safety information, please refer to our Material Safety Data Sheet. (MSDS).

DISCLAIMER

The Information provided on this data sheet is not intended to be complete and is provided as general advise only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continues product development.

NOTE :- ADDITIONAL INFORMATION WILL BE AVAILABLE ON REQUEST.