



Crown Air Drying / Stoving Zinc Chromate Primer (Y/G)

FEATURES / BENEFITS

Based on blend of premium quality binders and pure zinc chrome, this primer has very good adhesion & gives excellent corrosion resistance to metal.

RECOMMENDED USAGE

It can be used as an under coat on all metal surfaces for high corrosion resistance.

COVERAGE (DFT SINGLE COAT 20 TO 25 MICRONS)

Crown Air Drying / Stoving Zinc Chromate Primer : 200 to 260 sq. ft. (1 coat).

SHADE RANGE

Yellow / Green - Liquid.

GLOSS LEVEL

Crown Air Drying / Stoving Zinc Chromate Primer - Matt Finish.

DRYING TIME :

Touch Dry : 30 Mins.
Tack Free : 3 Hours.
Hard Dry : Overnight (24 Hours).

PACKING SIZE

500 ml., 1 Lt., 4 Lt., 20 Lt.

PAINTING

Single coat on well prepared & cleaned metal surface. (Two coats if required).

DILUTION

By Volume
8 to 10% (Brushing).
15 to 20% (Spraying).

THINNER

Use Champion Paints Thinner or Mineral Turpentine Oil.

(Thinner no.101).

SURFACE PREPRATION

Surface should be free from dust, dirt, grease, rust, moisture and loose particles for excellent result. Use Champion Paints thinner (Thinner no.101). Apply two coats.



Crown Air Drying / Stoving Zinc Chromate Primer (Y/G)

SAFETY PRECAUTION

Avoid contact with eyes and skin. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use barrier cream. Ensure that there is adequate ventilation in the area where the product is being applied. Do not breathe in vapour or spray mist. This product is flammable. Keep away from sources of ignition. Do not smoke. Take precautionary measures against static discharge.

FIRST AID

Eyes : In the event of accidental splashes, flush eyes with warm water immediately and seek medical advise.
Skin : Wash skin thoroughly with soap and water or approved industrial cleaner. Do not use solvents or thinners.
Inhalation : Remove to fresh air, loosen collar and keep patient rested.
Ingestion : In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

For further safety information, please refer to our Material Safety Data Sheet. (MSDS).

DISCLAIMER !

The Information provided on this data sheet is not intended to be complete and is provided as general advise only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of substrate, or other factors affecting the use if this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continues product development.

NOTE :- ADDITIONAL INFORMATION WILL BE AVAILABLE ON REQUEST.



CHAMPION COATINGS PVT. LTD.

I/29, G.I.D.C., Vithal Udyognagar - 388121, (GUJ.) India. Ph : (02692) 236330/236085
E-mail : info@championpaintsindia.com Website : www.championpaintsindia.com